



3 HP ROTARY PHASE CONVERTER

POWER, REDEFINED.

Industrial three-phase capability from the single-phase service already in your building - sized for 3 HP of running capacity.

DESIGNED AND BUILT IN PHOENIX, ARIZONA

INDUSTRIAL GRADE IS OUR STANDARD

[EXPLORE THE SERIES](#)

THE GP3 PLATFORM

THREE-PHASE POWER. WITHOUT THE UTILITY WAIT.

The GP3 converts 230 V single-phase service into balanced 230 V three-phase power for shops, farms, and industrial equipment with up to 3 HP of combined running load.



BUILT FOR THE REAL LOAD

3 HP RUNNING
1.5 HP STARTING

TEFC cast-iron idler. NEMA 4 sealed controls. Factory wiring, lifetime limited warranty, and direct sizing support.

230 V

SINGLE-PHASE INPUT

230 V

THREE-PHASE OUTPUT

10 KVA (30A)

PUBLISHED SERVICE

10 MIN - 30 MAX

BREAKER RANGE

WEATHER-READY

NEMA 4 / IP65-class enclosure

CONTINUOUS DUTY

TEFC industrial idler motor

PRECISION BALANCED

Voltage tuned for real equipment

DIRECT SUPPORT

Sizing and installation guidance

ONE PLATFORM. EIGHT PURPOSE-BUILT OPTIONS.

CHOOSE HOW YOUR GP3 BEHAVES.

Select the control and voltage package that matches the equipment, workflow, and service available at the site.



GP3NL

AUTO RESTART

Returns the converter to ready operation after power is restored.



GP3PL

MONITORED STARTER

Voltage monitor, magnetic starter, and Start / Stop controls.



GP3NLA

AUTOLINK CONNECTION

Automated connections for transformers, compressors, and equipment.



GP3NLA+

PARALLEL EXPANSION

Add another converter in parallel to expand capacity.



GP3NLTA

AUTOMATED PACKAGE

Converter and transformer package with AutoLink automation.



GP3NLTA

230 V TO 460 V

Factory-matched 3 kVA transformer package.



GP3DZ

DUALZONE

Two equal generators for staged starting and expanded running capacity.



GP3AS

AUTOSTART + AUTOOFF

Runs only when connected equipment calls for power.

GP3 ELECTRICAL + EQUIPMENT DATA

DIMENSIONS YOU CAN PLAN AROUND.

Published catalog values shown. Final ordered Phoenix production outline controls installation details.

NEMA 4 CONTROL PANEL

12 in x 10 in x 6 in



15 lb | wall mount

3 HP TEFC IDLER

Production outline controls



TEFC | 65 lb

3 kVA TRANSFORMER

230 V to 460 V package



optional package | outline controls

GENERAL + CONSTRUCTION

RATED OUTPUT	3 HP
MOTOR OUTPUT	2.2 kW
FREQUENCY	50 / 60 Hz
MOTOR ENCLOSURE	TEFC
MOTOR FRAME	TEFC
IDLER SIZE	Production outline controls
IDLER WEIGHT	65 lb
PANEL ENCLOSURE	NEMA 4 / IP65
PANEL SIZE	12 in x 10 in x 6 in
PANEL WEIGHT	15 lb
MOUNTING	wall
WARRANTY	lifetime limited

SINGLE-PHASE INPUT

VOLTAGE INPUT	230 V, 1-phase
SERVICE	10 KVA (30A)
BREAKER RANGE	10 MIN - 30 MAX
COPPER CONDUCTOR	10 AWG (under 50 ft)
IDLER CONDUCTOR	12 AWG
MAX STARTING LOAD	1.5 HP
RUNNING LOAD	3 HP
DISTANCE BASIS	under 50 ft
FINAL PROTECTION	order drawing
INSTALLATION	electrician / AHJ
GROUNDING	NEC / local code
TERMINALS	production drawing

THREE-PHASE + PACKAGES

BASE OUTPUT	230 V, 3-phase
RUNNING CAPACITY	3 HP
STARTING CAPACITY	1.5 HP
NL CONTROL	Auto Restart
PL CONTROL	monitor + mag starter
NLA CONTROL	AutoLink
NLA+ CONTROL	parallel expansion
AS CONTROL	AutoStart + AutoOff
NLT OUTPUT	460 V, 3-phase
TRANSFORMER	3 kVA
VOLTAGE BALANCE	load tuned
FINAL RATINGS	order drawing

ENGINEERING RELEASE NOTE

Conductor size, overcurrent protection, mounting holes, clearances, terminals, transformer orientation, and enclosure dimensions must be confirmed from the final Phoenix production drawing and reviewed by the installing electrician for the locally adopted NEC and AHJ requirements.

UL Listed panels are optional on all models.

800-417-6568